

IN THE CLAIMS:

Please amend the claims as follows:

1. (currently amended) A method of ~~detecting rotation~~ confirming operation of at least one ~~printer~~ printing system component, comprising:

forming at least one pattern on a marking material receiving part;

~~moving~~ inspecting said marking material receiving part ~~past~~ with a sensor configured to detect the presence of said pattern;

confirming operation of at least one printing system component based on detection of said pattern ~~sensing said marking material receiving part~~ with said sensor; and

selectively operating or disabling a printing system depending on whether said sensor signals ~~in response to a~~ positive detection of said pattern.

2. (currently amended) The method of claim 1, further comprising moving said marking material receiving part past said sensor to inspect for said pattern ~~preventing an operation of said printing system if said print pattern is not detected.~~

3. (original) The method of claim 1, wherein said pattern comprises a line.

4. (original) The method of claim 1, wherein said marking material receiving part comprises a transfer belt.

5. (original) The method of claim 1, wherein said marking material receiving part comprises a media sheet.

6. (original) The method of claim 5, wherein said media sheet comprises one of a sheet of paper or a plastic sheet.

7. (original) The method of claim 1, wherein said sensor is further configured to perform a color plane registration operation.

8. (currently amended) The method of claim 1, wherein said forming and said ~~sensing~~ inspecting said marking material receiving part is performed during a startup of said printing system.

9. (original) The method of claim 1, wherein said component comprises a rotating printer cartridge component.

10. (original) The method of claim 9, wherein said rotating printer cartridge component comprises an organic photo conductor.

11. (currently amended) A method of detecting rotation of at least one printer component, comprising:

forming a pattern on a marking material receiving part;

inspecting said marking material receiving part with a sensor configured to detect the presence of said pattern;

~~The method of claim 1, further comprising:~~

~~detecting a rotation~~ confirming operation of a plurality of printer components based on detection of said at least one pattern;

wherein said ~~detecting a rotation~~ confirming operation of a plurality of printer components includes forming a plurality of patterns on said marking material receiving part, each of said plurality of patterns corresponding to one of said plurality of printer components; and

preventing an operation of said printing system if one or more of said patterns is not detected.

12. (original) The method of claim 11, wherein said plurality of components comprise organic photo conductors.

13. (original) The method of claim 11, wherein said patterns comprise a series of spaced lines.

14. (original) The method of claim 11, wherein said marking material receiving part comprises a transfer belt.

15. (original) The method of claim 11, wherein said marking material receiving part comprises a media sheet.

16. (original) The method of claim 15, wherein said media sheet comprises one of a sheet of paper or a sheet of plastic.

17. (original) The method of claim 11, wherein said sensor is further configured to perform a color plane registration operation.

18. (original) The method of claim 11, wherein forming said pattern is performed during a startup of said printing system.

19. (original) The method of claim 11, wherein said components comprise rotating print cartridge components.

20. (currently amended) The method of ~~claim 11~~ claim 19, further comprising providing a prompt if one or more of said patterns is not detected, wherein said prompt is configured to prompt the reengagement of said print cartridges.

21. (original) The method of claim 20, further comprising reengaging said print cartridges.

22. (original) The method of claim 21, wherein said reengaging said print cartridges restarts said method.

23. (original) A method for starting up a printing system, comprising:
conducting a rotation detection operation, said rotation detection operation including forming a plurality rotation detection marks on a marking material receiving part corresponding to a plurality of print cartridges, conveying said marking material receiving

part past a sensor to detect a presence of said rotation detection marks, and preventing an operation of said printing system in response to a non-detection of said pattern; and

performing a color plane registration operation, said color plane registration operation including forming a plurality of alignment marks on said marking material receiving part, and conveying said marking material receiving part past said sensor.

24. (original) The method of claim 23, further comprising continuing an operation of said printing system in response to a detection pattern.

25. (original) The method of claim 23, wherein said rotation detection marks comprise a subset of said alignment marks.

26. (original) The method of claim 23, wherein said rotation detection marks are separate from said alignment marks.

27. (currently amended) A printing system, comprising:
a plurality of print cartridges, ~~each of said print cartridges having a developer and an organic photo-conductor;~~
~~at least one print cartridge~~ configured to form a rotation detection ~~and an alignment~~ mark on a marking material receiving part during a startup operation;
at least one sensor configured to sense said rotation detection ~~and alignment~~ marks; and
a controller configured to selectively operate or disable said printing system in response to whether said sensor signals positive detection of said rotation detection marks ~~control a rotation detection process and a color sub-image alignment process.~~

28. (original) The system of claim 27, wherein said plurality of print cartridges comprise a cyan ink filled print cartridge, a magenta ink filled print cartridge, a yellow ink filled print cartridge, and a black ink filled print cartridge.

29. (original) The system of claim 27, wherein said marking material receiving part comprises an intermediate transfer belt.

30. (original) The system of claim 27, wherein said marking material receiving part comprises an electronic transfer belt.

31. (original) The system of claim 27, wherein said sensor comprises an optical sensor.

32. (original) The system of claim 27, wherein said sensor comprises a density sensor.

33. (original) A printing system, comprising:
means for forming a rotation detection mark;
means for detecting the presence of said rotation detection mark; and
means for selectively preventing operation of said printing system if said rotation detection mark is not detected by said means for detecting.

34. (original) The printing system of claim 33, further comprising means for allowing an operation of said printing system in response to a detection of said detection marks.

35. (original) The printing system of claim 33, wherein said means for forming rotation marks further comprises means for forming alignment marks.

36. (original) The printing system of claim 35, wherein said means for detecting said rotation detection marks is also configured to detect said alignment marks.

37. (new) The method of claim 11, further comprising providing a prompt to a user if one or more of said patterns is not detected.

38. (new) The method of claim 11, wherein confirming operation of a plurality of printer components comprises confirming rotation photoconductive drums in respective print cartridges.

39. (new) The method of claim 11, further comprising moving said marking material receiving part past said sensor to inspect for said at least one pattern.

40. (new) The method of claim 1, further comprising providing a prompt to a user if said pattern is not detected.

41. (new) The method of claim 1, wherein confirming operation of at least one printing system component comprises confirming rotation of a photoconductive drum in one or more respective print cartridges.

42. (new) The system of claim 27, wherein said sensor is also used by said controller to perform color plane registration.

43. (new) The system of claim 27, further comprising an interface through which a user is prompted if said sensor fails to detect said rotation detection marks.

44. (new) The system of claim 43, wherein said interface prompts said user to re-engage one or more of said print cartridges.

45. (new) A printing system, comprising:

- at least one print cartridge configured to form a rotation detection mark on a marking material receiving part during a startup operation, said mark indicating that components are rotating as intended within said at least one print cartridge;
- at least one sensor configured to sense said rotation detection mark; and
- a controller configured to selectively operate or disable said printing system in response to whether said sensor signals positive detection of said rotation detection mark.

46. (new) The system of claim 45, wherein said sensor is also used by said controller to perform color plane registration.

47. (new) The system of claim 45, further comprising an interface through which a user is prompted if said sensor fails to detect said rotation detection marks.

48. (new) The system of claim 47, wherein said interface prompts said user to re-engage said print cartridge.

49. (new) A method of preventing toner dump in a printing system, said method comprising:

with a print cartridge, attempting to form at least one pattern on a marking material receiving part;

inspecting said marking material receiving part with a sensor configured to detect said pattern; and

determining whether components in said print cartridge are rotating as intended based on whether said pattern is or is not detected.

50. (new) The method of claim 49, further comprising selectively operating or disabling said printing system depending on whether said sensor signals positive detection of said pattern.